Dirt Gravel and Low Volume

NUMBER

Road Program

Stream Crossing Documents Overview

Policy: 5/25 9am Standard: 5/26 9am Tech Manual: 5/27 9am

If you are reading this, then you are successfully seeing the webinar video. Webinar audio should be automatic through your computer (or click "join audio"), and options can be accessed in the "audio options" button on the bottom left. If your computer audio is not working, you can listen on your phone by dialing 646-876-9923.

CDGRS Steve Bloser


<u>SCC</u> Roy Richardson Justin Challenger Sherri Law






Reminders:

- Contracts signed before 7/1/22 must follow existing policy, not required to follow standard.
- Documents available online (prelim format), will be printed and mailed to CDs
- 6 Regional trainings Scheduled June through December.
 - Each training consists of 4 virtual and 2 in-field sessions over two weeks.
 - Trainings taken this year WILL COUNT for certification requirement that goes into place 7/1/2023 (currently a 3-year certification).
 - Full Details online, registration is open, limited to 15 per session. as of 5/23:
 - Indiana: 3 spots remaining
 - Elk/Clarion: Full
 - Potter: 7 spots remaining
 - Monroe/Susq: 8 spots remaining
 - Cumberland: 6 spots remaining
 - Lehigh: 10 spots remaining





TECHNICAL MANUAL





Technical Manual

- Intended as details on how to meet policy and standard
- Does not contain additional requirements not already specified in Policy or Standard.

Table of Contents

1.	INTRODUCTION:	7
	1.1 PA DIRT, GRAVEL AND LOW-VOLUME ROAD (DGLVR) PROGRAM	7
	1.2 Consequences of Poor Stream Crossings	8
	1.3 BENEFITS OF GOOD STREAM CROSSINGS:	10
	1.4 Importance of Channel Continuity and Aquatic Organism Passage	11
	1.5 "Bankfull Width" of a Stream	13
	1.6 Replacing a Stream Crossing with DGLVR Funding	14

Tech Manual: Ch 1, Introduction

Ch 1 Highlights:

- The "why". Impacts of poor crossings and benefits of a different approach
- Built on lessons from USFS and other states.
- Focus on "Stream Continuity" over "Aquatic Organism Passage". (and continuity will get you AOP)
- Overview of roles and introduction of policy and standard, and bankfull.





Figure 1.5 Bankfull Width

The bankfull width of a stream is typically equivalent to the width at the elevation where water begins to access its floodplain, and is usually

State	Туре	Entity	Year	Min Structure Width	Min Embedment (material in structure)
PA	Guidance	PA DCNR	2022	1.25 Bankfull Channel Width	20%
PA	Regulation	PA DEP	2013	x	6" or 1' depending on permit
СТ	Guidance	CT DEP	2008	1.2x Bankfull	1', or 20% if over 10'
MA	Regulation	Riverways Prog.	2012	1.2x Bankfull, + dry passage	2', or 25% for round pipes
ME	Regulation	ME DEP	2008	25-year flow	
ME	Guidance	USFWS	2017	1.2x Bankfull	2' or 20% (salmon areas only)
NH	Regulation	NH DES	2009	1.2x Bankfull +2' (bridge over 16')	1' – 2', 25% for round pipes
NY	Guidance	NY DEC	?	1.25x Streambed Width	20%
VT	Guidance	VT FWD	2007	Bankfull + size of bank rocks	
GA	Guidance	GADNR	2012	Average channel width	20%
NC	Standard	NC DOT	2003	x	1', or 20% if under 4'
SD	Guidance	SD DOT	2011	1.2 Bankfull	1′
CA	Regulation	CA F&G	2007	1.5x Active Channel Width	20%
OR	Standard	OR DOT	2014	1.25 Ordinary High Water Width	20%
WA	Regulation	?	?	1.2x Bankfull +2'	20%
AZ	Guidelines	AZ F&G	?	Span floodplain with dry passage	17% (1/6 structure height)
RI	Guidance	RI DOT	2019	1.2x Bankfull	2' or 20%
FHWA	Guidelines	US FHWA	2010	x	Structure dependent (2', 20%, 30%)

Figure 1.3 Minimum Structure Size and Minimum embedment (depth of material) from various entities in other regions of the United States



Typical Existing Undersized Structure: with reference reach and proposed "tie-ins"

A "reference reach" should contain at least three grade controls and be located outside of the influence of the culvert. Determent tiein points that provide the best continuity of slope through the structure, upstream and downstream.

Tech Manual: Ch 2, DGLVR Stream Crossing Standard

2. DGLVR STREAM CROSSING DESIGN AND INSTALLATION STANDARD17

Ch 2 Highlights:

- Provides line-by-line explanation to the Standard.
- This is what we used in yesterday's webinar on the Standard.

IV. I. Consider floodplain connectivity when necessary (e.g., high water by-pass, overflow pipes, etc.). Floodplain- or overflow pipes must be placed a minimum of one bankfull-width distance outside of the bankfull channel

In most cases, a wider-than-bankfull width structure will be sufficient to accommodate high flow events. There are situations, however, such as wetland complexes and braided channels, where additional floodplain connectivity should be implemented. This could be accomplished using additional pipes (floodplain pipes, not a multiple pipe crossing), a French mattress, a highwater bypass, or other conveyance. However, it is important that such structures are not placed close enough to the new stream crossing structure to function as a multiple-opening stream crossing structure, which is why the DGLVR Stream Crossing Standard specifies a minimum distance from the bankfull channel for installed floodplain- or overflow pipes.

IV. J. Structures must be designed and constructed to accommodate the passage of aquatic organisms through the structure.

In most cases, aquatic organism passage will be obtained by achieving channel continuity upstream, <u>through</u>, and downstream the structure by following the requirements of the DGLVR Stream Crossing Standard related to reestablishing slope, low-flow channels, bank margins, grade control, and **bedforms** reflective of the reference reach.

IV. K. Round pipes over 36" in diameter may not be utilized for stream crossings.

Round plastic pipes, by design, are intended to move water rapidly and flush the pipe clean. While this is

www.dirtandgravelroads.org

Tech Manual: Ch 3, Initial Assessment and Planning

3.	INITIAL SITE ASSESSMENT AND PROJECT PLANNING	27
	3.1 Stream Specific Discussion Points	
	3.2 Stream Measurements and Structure Eligibility	
	3.3 EXEMPTIONS FROM THE DGLVR STANDARD	
	3.4 PROPOSED PROJECT SCOPE OF WORK	
	3.5 SCC NOTIFICATION	

Tech Manual: Ch 3, Initial Assessment and Planning

Ch 3 Highlights:

- Determining eligibility for replacement
- Details on exemptions.
- **Pre project considerations**
 - **Realistic timelines** •
 - Off-ROW
 - **Prevailing Wage** ullet
 - Potential project and engineering costs
 - Permitting ${}^{\bullet}$
 - Likelihood of funding •

www.dirtandgravelroads.org

SCC notification ۲

Pre-Application Meeting Checklist for Stream Crossings LVR Additional Attendees: Additional Attendees: Summarizes discussion points for an initial on-site meeting prior to application. More information in Chapter 3 o Publicly owned road (Is road open to public vehicles at least 2 weeks per year?) LVR <500 ADT (count required before contract can be signed) ESM certification (person in charge of project for applicant has recent (last 5 years) ESM certificatio Complete stream crossing evaluation form and keep copy in file Automatically eligible (Existing Structure under 4', see section 7.1.2.2) Structure opening to bankfull channel width ratio of 75% or less?


Other Resources:

- **Checklist**: Pre-App meeting
- Tech Bulletin: Bankfull Width Determination

Technical Bulletin Bankfull Width Determination



BANKFULL FLOW (STAGE OR ELEVATION) – This flow stage is determined by the which the stream accesses the floodplain. This point is typically indicated by deposits of active scour mark, a break in stream bank slope, perennial vegetation limit, rock discol exposure. The bankfull flow is also known as the channel-forming or dominant dischart that transports the most sediment over time and is the most effective in shaping and m stream channel. The bankfull flow roughly corresponds to a 1.5-2 year recurrence inte CHANNEL WIDTH is the width of the channel at the bankfull flow elevation.




4.	SITE ASSESSMENT	
	4.1 LONGITUDINAL PROFILE	
	4.2 CROSS SECTIONS	
	4.3 THE REFERENCE REACH	
	4.4 RECORDING SITE ASSESSMENT DATA	
	4.5 SITE ASSESSMENT ANALYSIS TOOL	

Tech Manual: Ch 4, Site Assessment

Ch 4 Highlights:

- **Longitudinal Profile**
- **Cross Sections**
- **Reference Reach**
- Data analysis



www.dir tanugraven oads.org

Other Resources:

- Will be major focus of stream trainings
- Tech Bulletin: Site Assessment: Long Pro and Cross Sections

Technical Bulletin Site Assessment - Longitudinal Profile Center for Dirt and Gravel Road Studie

9/20/

LONGITUDINAL PROFILE (LONG-PRO) – A survey conducted upstream, downstream, and through existing structure to determine the stream channel features that are critical to a successful struct replacement, such as: channel and structure slope, grade control types and spacing, scour depth, ti locations, aggregation wedges, plunge pools, vertical offset of the structure, available cover, and more. CROSS-SECTION SURVEY - A survey conducted across the channel (perpendicular to the thalwey produce a graphical representation of channel dimensions including shape, depth and width.

Other Useful Definitions:

grade control: instream features such as large rocks, logs, or manmade structures that control channel

During high water, natural stream channels move sediment (rock, gravel, sand, STREAM CONTINUITY large wood, nutrients and debris downslope through the landscape. Over time, under road/stream crossings often disrupt this natural channel movement or continu depositing sediment at the inlet, creating a plunge pool at the outlet, and therefore cr a 'vertical offset' between inlet and outlet streambed elevations. When replacing undersized structures, it is necessary to survey upstrea downstream of the structure itself. Stream characteristics such as slope, grade cont and spacing, channel shape, and bed composition should be consistent throu

5.	GRANT APPLICATION FOR REPLACEMENT STRUCTURES	. 37
	5.1 STRUCTURE SELECTION	37
	5.1.2 OTHER CONSIDERATIONS AFFECTING STRUCTURE SELECTION	39
	5.2 AGGREGATES	40
	5.3 STREAMBED (SUBSTRATE)	41
	5.4 EROSION AND SEDIMENT CONTROL MATERIALS	41
	5.5 DRAINAGE AND OTHER SUPPORT MATERIALS	42
	5.6 EQUIPMENT	42
	5.7 LABOR	42
	5.8 ENGINEERING	43
	5.9 BUDGETING FOR COST INCREASES	43

Tech Manual: Ch 5, Grant Application

Ch 5 Highlights:

- Estimating quantities and costs
- Structure Selection: size, type
- Grade controls
- Streambed
- Other materials
- Labor (contracted vs muni)
- Engineering

Goal is to get a good estimate of costs for contracting. Final design determined by engineer.

www.dirtandgravelroads.org

Other Resources:

- Tech Bulletin: Structure Selection
- Tech Bulletin: Grade Control
- Tech Bulletin: Streambed Material

12/21

Technical Bulletin Center for Dirt and Gravel Road Studies Structure Selection for Stream Crossings STRUCTURE SELECTION for ROAD STREAM CROSSINGS – Selecting an appropriate structure for STRUCTORE SELECTION TO ROAD STREAM CROSSINGS - Selecting an appropriate survive to crossing replacement will reduce maintenance, improve stream continuity, and increase longevity of the and vary by material and design. Always consult WHY DOES STRUCTURE SELECTION MATTER? Every site presents unique challenges and structure selection is a critical component to the success of any stream crossing project. Selecting the proper structure is important in providing continuity of the stream through the road crossing and providing a long-term, low-maintenance solution to the road owner. A property selected and designed crossing will meet the following objectives: ✓ 1.25 bankfull width minimum opening at bankfull elevation Stable grade controls and stream bed in the structure Stream continuity and passage of aquatic organisms Bank margins established to create a low-flow Capacity to pass 100-year discharge (Q100) at 80% of the channel and protect the structure from scour. finished opening height

STRUCTURE SELECTION CONSIDERATIONS STRUCTURE SELECTION CONSIDERATIONS Longitudinal Profile: A longitudinal profile conducted upstream Longitudinal Profile: A longitudinal profile design practice that ad downstream of the structure is a required design practice that ad downstream of the structure is a required design practice that ad downstream of the structure is a required design practice that ad downstream of the structure is a required design practice that ad downstream of the structure is a required design practice that additional profile downstream of the structure is a required design practice that additional profile downstream of the structure is a required design practice that additional profile downstream of the structure is a required design practice that additional profile downstream of the structure is a required design practice that additional profile downstream of the structure is a required design practice that additional profile downstream of the structure is a required design practice that additional profile downstream of the structure is a required design practice that additional profile downstream of the structure is a required design practice that additional profile downstream of the structure is a required design practice that additional profile downstream of the structure is a required design practice that additional profile downstream of the structure is a required design practice that additional profile downstream of the structure is a required design profile downstream of the structure is a required design profile downstream of the structure is a required design profile downstream of the structure is a required design profile downstream of the structure is a required downstream

Tech Manual: Ch 6 & 7, Ranking and Contracting

6.	QUALITY ASSURANCE BOARD (QAB) RANKING AND REVIEW	44
	6.1 CONSIDERATIONS FOR RANKING STREAM CROSSING PROJECTS	.44
	6.2 PRE-SCREENING STREAM CROSSING REPLACEMENTS (OPTIONAL)	.45
7.	CONTRACTING	46
	7.1 PRIOR TO CONTRACTING	.46
	7.2 WRITING A CONTRACT	.46
	7.3 REVIEWING AND SIGNING A CONTRACT	.46
	7.4 AMENDING A CONTRACT	.46

Ch 6&7 Highlights:

- Fairly "normal" DGLVR procedures
- Ranking and evaluation considerations
- Contracting and amendments

Tech Manual: Ch 8, From Contracting to Construction

8.	FROM CONTRACT TO CONSTRUCTION	7
	8.3 DESIGN SITE ASSESSMENT (SURVEY)	8
	8.4 CONSERVATION DISTRICT REVIEW OF PLANS AND SPECIFICATIONS	8
	8.5 BIDDING FOR MATERIALS AND PROJECT IMPLEMENTATION	9
	8.6 SITE SHOWING FOR INSTALLATION	9
	8.7 GRANT RECIPIENTS REPLACING A STRUCTURE USING THEIR OWN WORKFORCE	0
	8.8 PRE-CONSTRUCTION MEETING	0
	8.9 TRAFFIC CONTROL	0

Tech Manual: Ch 8, From Contracting to Construction

Ch 8 Highlights:

- Engineering and RFP(optional)
- **Engineering survey**
- CD review of plans
- Bidding
- CD review of bid
- Site showing (required to attend if held)

Re:

Pre-design and pre-construction meetings (required)

Pre-Design Mentine Classic	< <date></date>
Pre-Design Meeting Checklist for Stream Crossings	
Applicant Reps: Road Name:	
CD Reps:	< <appl< th=""></appl<>
Additional Attendees:	CON
Summarizes discussion points for an on-site meeting prior to project design. Mor Stream Crossing Replacement Technical Manual.	< <con <<city< th=""></city<></con
Project-Specific Discussion Dates	A CHI

- Discuss/Introduce Goals & Objectives of DGLVR Program Stream Cr
 - Restore stream through road profile (stream continuity) Flood resiliency and ensures lifespan
 - Reduced Maintenance
 - Full Aquatic Organism Passage
- Provide Design Engineer with a copy of:

 - Stream Crossing Design & Installation Standard Stream Crossing Replacement Technical Manual

Project Management and Meetings

- Design engineer is required to attend the pre-design meeting at the

<<APPLICANT NAME>> <<PROJECT CONTACT NAME>> <<CONTACT NAME ADDRESS LINE 1>> <<CONTACT NAME ADDRESS LINE 2>> <<CITY, STATE ZIPCODE>>


DGLVR Program Stream Crossing Design & Installation Standard Bid Documents and/or Shop Drawings Consistency Letter << PROJECT NAME, APPLICANT NAME>>

Dear <<PROJECT CONTACT NAME>>:

The <<BLANK COUNTY>> Conservation District (District) has reviewed the above refere for consistency with the permit and construction plans that were previously reviewed fo the PA Dirt, Gravel and Low-Volume Road (DGLVR) Program Stream Crossing Desi Standard. This review is only to check the documents for meeting the DGLVR Stream Installation Standard and is not intended as a check on any design calculations. termined the Bid Documents and/or Shop Drawings contain sufficient detail to doc

Other Resources:

- **Templates:**
 - RFP for engineering
 - CD permit review letter
 - CD bid package review letter
 - **Checklists:**
 - **Pre-design Meeting**
 - Permit review
 - **Bid-package review**
 - **Pre-construction Meeting**



Tech Manual: Ch 9, Construction and Inspection

9.	CONSTRUCTION AND INSPECTION	. 51
	9.1 GENERAL INSPECTION & CONTRACT AUTHORITY	51
	9.2 Engineers' Inspection Requirements	51
	9.3 SAFETY	51
	9.4 EROSION AND SEDIMENTATION CONTROL	52
	9.5 DEWATERING	52
	9.6 EXCAVATION	52
	9.7 CONSTRUCTION SURVEY STAKEOUT AND ACCURATE SURVEYS	53
	9.8 Structure Foundation / Bed Preparation	53
	9.9 STREAMBED RECONSTRUCTION	53
	9.10 MATERIAL INSPECTION	54
	9.11 BACKFILL FOR THE REPLACEMENT STRUCTURE	55
	9.12 RESTORING STREAM FLOWS TO THE NEW STRUCTURE	
	9.13 HEADWALL, ENDWALL, AND WINGWALL INSTALLATION	56
	9.14 SITE RESTORATION AND CLEAN UP	
	9.15 FEDERAL HIGHWAYS STRUCTURE INSPECTION (>20 FEET CLEAR SPAN OPENING)	56

Tech Manual: Ch 9, Construction and Inspection

Ch 9 Highlights:

- Inspection Requirements (engineer and CD)
- Logistics: safety, E&S, dewatering etc
- Structure placement
- Re-establishing stream
 - Grade Control
 - Bank Margins
 - Streambed substrate
- Backfill and cleanup

Technical Bulletin Streambed Restoration RESTORING NATURAL STREAMBED MATERIAL - Restor stream crossing replacement is a critical component of a succ the substrate that makes up the stream channel bottom. Fir survey, grade control features and shear stress calculations with to inform decision making on depth and sizing of material. WHY STREAMBED MATERIAL IS IMPORTANT It is important to simulate the natural streambed through the reco Control permeability to prevent the streamflow from going Provide continuity of slope and reconnect the stream char Create varied velocities across the cross-section of the str Dissipate energy and prevent excessive scour and materia Increase the lifespan of the structure Maintaining streambed material in the structure is the only wa subsurface layer urface

layer

particle size

Other Resources:

- Tech Bulletin: Grade Control
- Tech Bulletin: Streambed Material
- Checklist: Construction Inspection

standa
l standa
nstruct Stages
Stages
ress a
lress a tely no all par
all par

www.dirtandgravelroads.org

Tech Manual: Ch 10, Final Inspection and "As Built" Notes

10. FINAL INSPECTION AND AS BUILT NOTES	
10.1 FINAL ON-SITE INSPECTION	
10.2 PROJECT COMPLETION REPORT	
10.3 HABITAT RE-CONNECTIVITY	
10.4 FINAL ENGINEERING DOCUMENTATION	
10.5 FINAL PROJECT PAYMENT	

Ch 10 Highlights:

• Final inspection and completion report

www.dirtandgravelroads.org

• Documentation and payment

Other Resources:

Checklist: Final Inspection

		Creatings		LVR
a subtien/	Final Inspection Meeting Checklist f	or Stream Crossings		
Completion	n d Name	LAT/LONG:		
Applicant:	Final Inspection Meeting Checkinse		_ Date:	
I I want Rens!				
Replacement Tec	ndees:			
Final Site Insp	ection			
			normit red	uirements, a
0	See Site Inspection circulate appurtenances	s installed according to plan	, permit req	din children i
0	Stream crossing structure and app DGLVR requirements Stream restoration completed according to p	the environments 7	and DGLVR r	equirements
	Stream restoration completed according to p	lan, permit requirements, o	continuity	
•	Stream restoration completed according to p including low flow channel, stream banks, ar	nd grade control structures, according to plan and DGL	VR requirem	ents

Tech Manual: Ch 11, Monitoring and Maintenance

11. MONITORING AND MAINTENANCE	
11.1 MONITORING THE CROSSING	
11.2 MONITORING THE PHYSICAL STRUCTURE	
11.3 MONITORING THE STREAMBED	
11.4 MAINTENANCE AND REPAIR	60

Ch 11 Highlights:

- Site monitoring encouraged but NOT required
- Regular Maintenance: up to road owner
- Larger "repairs": May be funded at discretion of individual CDs

Tech Manual: Ch 12, Engineering Design Considerations


12.	ENGINEERING DESIGN CONSIDERATIONS	62
	12.1 PROJECT DESIGN	.63
	12.2 CONSTRUCTION DOCUMENTS	.77
	12.3 DESIGN SUBMITTAL FOR CONSERVATION DISTRICT	.81
	12.4 PERMITTING	.81
	12.5 BID DOCUMENTS	.82
	12.6 CONSTRUCTION INSPECTION AND CERTIFICATION	.84

Ch 12 Highlights:

- This chapter is intentionally repetitious of previous Chapters.
- Written with an engineer audience in mind
- More technical and design oriented
- Can give to design engineer
- This is where a lot of the "nitty gritty" lives

Other Resources:

- GP-11 Permit Memo
 - Raising the Road
 - Crossing realignment



APPENDICES

Appendix A. DGLVR Stream Crossing Design and Installation Standard Appendix B. Definitions and Acronyms Appendix C. Stream Crossing Evaluation Form Appendix D. Stream Continuity Sketches Appendix E. SCC GP-11 Permit Memo Appendix F. Editable Forms and Templates Appendix G. Checklists Appendix H. Technical Bulletins

Effective July 1, 2022



TECHNICAL MANUAL

- 1. Introduction
- 2. Understanding the standard
- 3. Initial Site Assessment
- 4. Longitudinal Profile Survey
- 5. Grant Application (Material Selection & Cost Estimation)
- 6. QAB Ranking & Review
- 7. Writing a Contract
- 8. From Contract to Construction
- 9. Installation and Constructions Inspection (active project oversight)
- 10. Final Inspection & As-built Notes
- 11.Maintenance
- 12. Engineering Design, Permitting, and Bidding a Stream Crossing

Technical Manual does not contain additional requirements not already specified in Policy or Standard.

Additional Questions?

