

**Dirt Gravel and Low
Volume Road Program**

WEBINAR

DSA Season

3/21/24

Starts at 9am

Dave Morrison - CDGRS

Steve Bloser - CDGRS

www.dirtandgravelroads.org

If you are reading this, then you are successfully seeing the webinar video. Webinar audio should be automatic through your computer (or click "join audio"), and options can be accessed in the "audio options" button on the bottom left. If your computer audio is not working, you can listen on your phone by dialing 646-876-9923.



Audio via Phone if needed: 646-876-9923

Webinar ID: 987 5482 6192



Driving Surface Aggregate

- Placement Season April through September
- 110,000 tons placed in 2023 (SCC funds only)
- @ \$40 a ton, that's \$4.4 Million or roughly 25% of overall DGR roject spending



DSA Season Prep



Purpose

- **Primer and reminder for DSA placement season starting April 1**
- **Discussion of new DSA Project Checklist**

RESOURCES:

DSA Certification: 2 page DSA certification form

DSA Specification: Material & Placement specs

DSA Handbook: More in depth DSA explanation

- Includes Request for Quote
- more details to come

All can be found on the CDGRS website including this webinar.

DSA RESOURCES:

DSA Handbook: More in depth DSA information

- includes Request for Quote
- www.dirtandgravelroads.org

Municipal DSA Quick Guide.

Municipal Quick-Guide to Driving Surface Aggregate
 The purpose of this document is to briefly outline the requirements and recommendations regarding placement of Driving Surface Aggregate (DSA) through the PA Dirt, Gravel, and Low Volume Road Maintenance Program (DGLVRP). Additional details can be found in the "DSA Handbook". Since the DGLVRP Program emphasizes "local control", potential applicants should always check with their local Conservation District for county-specific policies regarding DSA and other aspects of the Program.

Pre-project Logistics (Full Details in chapter 4 of DSA Handbook)

- Notify Conservation District of intent to apply.
- Conduct pre-application site-visit with Conservation District.
- The DGLVR Program focuses on long-term road and environmental improvements. Projects are **Required** to focus on drainage, road base, and environmental issues prior to DSA placement. DSA is NOT required on every project.

Purchasing DSA:

- o Normal bidding procedures apply.
- o Prevailing Wage applies to DGLVR projects over \$25,000. **Required**
- o Sample DSA "Request for Quote" in DSA handbook. Contact local Conservation District to determine any county specific requirements for DSA material or bidding procedures.
- o Notify Conservation District once DSA supplier is chosen. District and/or Program representative will test DSA to ensure it meets Program standards. **Required**

Road Preparation (Full Details in chapter 5 of DSA Handbook)

- Make provisions for road closure if possible (during placement and drying), and notify any residents.
- Drainage and base improvements must be done before DSA placement. **Required**
- Establish proper crown or cross-slope (1/2 to 3/4 inch per horizontal foot (4% - 6% slope)) in the road prior to grading. **Required**
- Establish adequate crown but is extremely tight.
- Do not grade beyond the edge of aggregate when possible.

How much DSA should I order?

DSA Needed (tons)	Road Width (ft)	Road Length (ft)	0.04 8" loose depth compacted to 6"
			0.03 6" loose depth compacted to 4 1/2"

Paver Considerations:

- o Track pavers are recommended, especially on steeper slopes.
- o Paver should be capable of placing entire road width in one pass. Avoid multiple lane placements if possible.
- o Paver must be able to match crown or cross-slope previously established in road base (1/2 to 3/4 inch per horizontal foot (4% - 6% slope)). **Required**
- o Place DSA in one uniform lift. **Required**

Grading Considerations:

- o Tailgate material in as uniform of a lift as possible, avoiding large piles.
- o Handle the material as little as possible with grader in attempting to establish road shape. Overworking DSA will cause it to segregate by size and it will not perform as desired.

Compaction (Full Details in chapter 6 of DSA Handbook)

- o Compaction requires optimum moisture. **Required**. Insure compaction occurs out. If excess material sticks to the roller drum, it may be too wet and so required before continuing compaction.
- o In vibratory roller is **required** for DSA compaction.

Finishing:

- o Passes should be done in static (non-vibratory) mode.
- o Vibratory mode should be done in vibratory mode.
- o Passes from the road edge towards the crown.
- o Passes from both sides, but do not "straddle" the crown with the roller.
- o Finishing using a density gauge is recommended, and the cost of testing can be covered by the DGLVRP grant.

Moisture (Chapter 7 of DSA Handbook)

- o Moisture in DSA should be higher than other materials and requires special care during placement to avoid segregation and instability. **Required**
- o Moisture should be checked during placement and installed during placement.

Paver placement

Reminder: 2023 DSA Changes:

Material

- Slight gradation change. #200 11%-15% (17% if PI <2)

Placement

- Placement Season April 1 through September 30 **unless approved by SCC – NO GUARANTEE!**
- Paver must place DSA in single pass (*paver still not required for jobs less than 500 tons*)

DSA Use and Overuse

- When DSA is used as part of a project, it should be the very last phase of the project.
- DSA alone does not constitute a comprehensive DGLVR Program project.



Purchasing DSA with DGLVR Funds:

- DSA must be independently sampled and tested
- 30-day notice time required for testing if CDGRS is doing the sampling.
- Help from Center is also available for testing or placement on request.

Purchasing DSA with DGLVR Funds:

- DSA must be independently sampled and tested
- **30-day notice** time required for testing if CDGRS is doing the sampling.

- **Helpful placement**

30 day notice is a minimum

Notify as soon as supplier is known

- Supplier needs time to make entire pile
- Time for sampling
- Time for testing
- Potential time for failures

How to sample a DSA pile

- Sampling and testing must be done on the (entire) specific pile that is supplying your project



How to sample a DSA pile

- Sampling and testing must be done on the (entire) specific pile that is supplying your project
- Sample the full pile required for your project, if your project requires 5,000 tons, it must be a 5,000-ton pile.
- Quarries must produce DSA piles in advance of delivery in order to allow time for sampling and testing
- Labs can get backlogged in construction season

Can a conservation district pull their own sample?

- **Yes. If a CD pulls their own sample, they must also pay for the lab testing.**
- **The costs of testing can be incorporated into the project cost or paid out of admin/education funds**
- **Sampling and testing can also be done, free of charge, by the Center's DSA Clearinghouse (more details on that later)**

How to collect a DSA sample...



- **Contact the Center and we will train at the quarry on how to properly pull a sample.**
- **Not as simple as just putting material in a bucket!!!**

How much do I need for a sample?

Proctor, gradation, plasticity



(2) $\frac{3}{4}$ full 5-gallon buckets (Minimum)

- More buckets necessary depending on pile size and required tests
- Too much sample is always better than not enough

How much do I need for a sample?

One additional bucket each for Soundness
And LA Abrasion if needed



pH testing is rare and can be run with minimal material

Lab Testing


- **Interested in sampling your own DSA?**
- **Let us know. We can share logistics of sample delivery or shipping, testing, etc.**

Lab Testing

- **Material must be tested by an independent lab (with no affiliation with the quarry or placement contractor) before delivery**
- **The testing lab must be currently certified by AASHTO or PennDOT**
- **Per the SCC specification, DSA shall not be placed without pre-delivery sampling and testing. This testing is key to catching any potential problems with the aggregate BEFORE it is placed.**

Lab Testing

- Example of lab results
- The lab looks at more sieves than just those in the specification
- This gives us a very clear snapshot of what is in the pile



ASTM Specifications called out may include: D421, D422, D1516, D2017, and D4318.

Lab Testing

Lot-dependent tests: **run on every pile**

- **Gradation** (size distribution)
- **Plasticity** (clay content)

Periodic test: **Proctor** (gives optimum moisture and max dry density)

Source-dependent tests: rarely needed

- **Toughness** (LA Abrasion)
- **pH**
- **Soundness** (resistance to freeze/thaw)

What happens if a sample fails?

Gradation

- If it's close to meeting the spec., re-sample and re-test. This is a common practice.
- If it fails a second time, a new pile will have to be made

The DSA spec:

Passing Sieve	Lower %	Higher %
1½ inch	100	-
¾ inch	65	97
#4 (¼ ")	30	65
#16 (1/16 ")	15	30
#200(1/200 ")	11	15*

SIZE FRACTION	MASS RETAINED	INDIVIDUAL PERCENT RETAINED	PERCENT PASSING
2"	0.0	0.0	100.0
1.5"	0.0	0.0	100.0
1"	856.0	8.1	91.9
¾"	866.0	8.2	83.6
½"	1192.1	11.3	72.3
3/8"	802.8	7.6	64.7
#4	1522.1	14.5	50.2
#8	1096.0	10.4	39.8
#16	751.0	7.1	32.6
<#16	3428.6		
<#200		WASH LOSS	13.3

Spec: 15-30

Gradation run on every pile

What happens if a sample fails?

Plasticity

- If plasticity fails, a new pile needs to be made after discussion of production methods
- Some quarries may never meet this part of the spec.

LIQUID / PLASTIC LIMITS OF SOIL - ASTM D 4318
DSA from

**Plasticity run
on every pile**

LIQUID LIMIT	22
PLASTIC LIMIT	15
PLASTICITY INDEX	7

Maximum allowable PI is 4 (or 2 if fines are 15-17%)

What happens if a sample fails?

LA Abrasion

- Find a new supplier. This property is a quality of the rock formation.
- Its possible a new seam of rock at the quarry may perform better. Let quarry test it first.

Maximum allowable abrasion loss is 45%

Toughness rarely run

LOS ANGELES ABRASION - AASHTO T 96					
2A from			Quarry		
A GRADING					
SIZE FRACTION	MASS	TOTAL MASS	MASS (+#12) AFTER	MASS LOSS	PERCENT LOSS
1 1/2" x 1"	1257.9	5012.5	2995.9	2016.6	40.2
1" x 3/4"	1251.4				
3/4" x 1/2"	1251.0				
1/2" x 3/8"	1252.2				

What happens if a sample fails?

Soundness:

- Find a new supplier. This property is a quality of the rock formation.
- Its possible a new seam of rock at the quarry may perform better. Let quarry test it first.

Maximum allowable soundness loss is 20%

Soundness rarely run

SODIUM SULFATE SOUNDNESS - PTM 510 m DSA from 4000 tons							
SIZE FRACTION	MASS BEFORE	# OF PCS	MASS AFTER	# OF PCS	PERCENT LOSS	STANDARD GRADING	CORRECTED LOSS
1" x 3/4"	1501.2	106	735.2	58	51.0	0.368	18.8
3/4" x 3/8"	1001.8		532.2		46.9	0.369	17.3
3/8" x #4	300.1		123.4		58.9	0.263	15.5
TOTAL PERCENT LOSS							51.6

What happens if a sample fails?

pH- Find a new supplier (one and done in most cases).

pH = 5.1, per EPA S-846 Method 9045

DSA SPEC: pH between 6 and 12.45

pH rarely run

DSA Clearinghouse



PURPOSE

- Provide a central point of contact between conservation districts and DSA suppliers.
- Provide DSA testing services when needed.
- Provide DSA education to conservation districts.
- Provide a central repository of DSA testing and placement data for the state to serve as a reference and avoid duplication of testing.

DSA Clearinghouse

DISTRICT RESPONSIBILITY



- Contact the Center for Dirt and Gravel Road Studies when a potential DSA supplier is chosen, at least 30 days before desired placement date.
- Notification can be made utilizing the DSA Purchase Notification Form, provided in Appendix D in the DSA Handbook, or on the Center's website.
- If districts choose to sample their own DSA, they should share testing results with the Center in order to provide a more comprehensive statewide database and avoid duplicate testing.

DSA Clearinghouse

DISTRICT RESPONSIBILITY



- Contact the Center for Dirt and Gravel Road Studies when a potential DSA supplier is chosen, at least 30 days before desired placement date.



30 day notice is a minimum
Notify as soon as supplier is known

- Supplier needs time to make entire pile
- Time for sampling
- Time for testing
- Potential time for failures

- Notification of
- Notification of
- Handbook, o
- If districts ch
- testing result
- comprehensive statewide database and avoid duplicate testing.

re

DSA Notification: CD portion

PA Dirt, Gravel, and Low-Volume Road Maintenance Program

Driving Surface Aggregate (DSA) Purchase Notification Form

This form is for Conservation Districts to provide notice to the PSU Center for Dirt and Gravel Road Studies (CDGRS) of upcoming DSA placement projects. The top portion of this form is to be completed and returned to dirtandgravel@psu.edu or fax: 814-863-6787.

CONTACTS	Entity	Person	Phone	E-mail
Cons. District:	_____	_____	_____	_____
Grant Recipient:	_____	_____	_____	_____
Quarry	_____	_____	_____	_____
Placement Cont.:	_____	_____	_____	_____

PLACEMENT DETAILS

Tons DSA to be placed: _____ tons Estimated Placement Date: _____

Est. Total DSA Costs: \$ _____

Placement Method: Motor-paver Other: _____

Road Name(s) / #(s): _____

If the Center for Dirt and Gravel Road Studies is to perform DSA testing, the Conservation District must provide at least 30 days notification before expected placement. This will allow the Center to coordinate with the quarry and perform any quality control steps necessary prior to and during placement. This could include lab testing for plasticity index, gradation, proctor (for maximum dry density and optimum moisture content), LA Abrasion, pH, soundness, and field testing for moisture and compaction, as well as site visits during placement. If a Conservation District chooses to sample and test a DSA stockpile they should share the testing results with the Center to improve records statewide. This completed form is to be included with the certification from the quarry in the project file. Any entity producing DSA must obtain the components from a source or quarry that complies with the SCC DSA Standard and Specifications. **Quarries cannot be certified for DSA, only specific stockpiles of DSA can be certified.**



dcm35@psu.edu

DSA Notification: CDGRS portion

PA Dirt, Gravel, and Low-Volume Road Maintenance Program

DSA Notification Form

CENTER USE ONLY:

Date Notification Received: _____ Received by: _____

Discussed with CD: YES / NO _____

Discussed with Quarry: YES / NO _____

Visited Quarry: YES / NO _____

Testing Completed: YES / NO _____

Tests Performed: PI __, Gradation __, Proctor __, LA Abrasion __, ph. __, Soundness __, Other _____

Results reviewed with CD: YES / NO _____

Results within SCC DSA spec: YES / NO _____


Completed By: _____ Date Completed: _____

with the certification from the quarry in the project file. Any entity producing DSA must obtain the components from a source or quarry that complies with the SCC DSA Standard and Specifications. **Quarries cannot be certified for DSA, only specific stockpiles of DSA can be certified.**

DSA Clearinghouse

POTENTIAL SERVICES PROVIDED

- Visiting and talking with quarries and CD to ensure they understand the DSA requirements.
- Collecting samples from the quarry and performing testing to ensure DSA meets all material requirements before delivery and placement.
- Providing contractor education on DSA.
- Providing **on-site assistance** during DSA placement.
- Education of Conservation District staff on DSA sampling, testing, and placement.
- Troubleshooting.
- Identifying potential DSA suppliers if you are having trouble finding DSA in your area



Get on the schedule as far out as possible.

NEW DSA Project Checklist/Walkthrough for CDs

- 3-pages
- Sent in webinar reminder
- Posted online

Surface Aggregate Project Checklist for Conservation Districts

This document is intended to serve as a guide for Conservation Districts to plan and implement successful Surface Aggregate (DSA) placement as part of a DGLVR project. This is intended as a guide and is not a list of required actions. Items listed as required below are defined in policy or the DSA specification.

Application

Drainage and base first: The DGLVR Program's focus is on long-term road and environmental improvements. Projects are Required to address any drainage, road base, and environmental issues prior to DSA placement. DSA is NOT required on every project. If used, DSA should be the LAST part of a project after all potential drainage and base improvements have been made.

Meet with municipality, preferably on-site to discuss prior to application submittal:

- Discussion points:
 - **Timing:** application, drainage work, lab testing, placement dates, placement window (April-Sep). Consider letting large fill projects settle for a season before placing DSA (could place DSA as a second contract, local decision up to CD)
 - **Details:** Proposed project length, available budget, DSA depth, width, thickness, and tonnage. Use of paver, required for placements of 1,000 tons or more.
 - **Potential suppliers and placement contractors**
 - **Road preparation:** in addition to drainage, what road surface prep (fill, grading) will need to be done prior to placement, and who will be responsible.
 - **Compaction:** Will compaction testing be utilized (costs can be built into grant application)?

How much DSA should I order?

$$\text{DSA} = \text{Road Width} \times \text{Road Length} \times \begin{matrix} 0.04 & \text{8" loose depth} \\ & \text{compacted to 8"} \\ 0.03 & \text{6" loose depth} \end{matrix}$$

2/3/21

- **Too Wet:** If excessive water is running out of the delivery truck and the material is too wet. Ideally, over wet material should not be placed. If over wet material is placed and road opening may need to be delayed depending on weather conditions.
- **Too Dry:** If material is too dry to compact, it should be sent back. Material that segregate and be impossible to compact, resulting in a reduced lifespan for the DSA.
- **Compaction testing:** Compaction testing with a nuclear density gauge, although not required, is the best way to determine aggregate moisture. It is easier to send wet/dry trucks back with testing.
- **Making Adjustments:** Contact the quarry to make adjustments to moisture. Take several trucks before adjustments at the quarry are seen on the road. Send trucks back to send trucks back or visit the quarry to discuss.

Final Road Preparation: Grading and establishing final crown (week of placement). Establishment of paving notches and keys to support edge of DSA placement (day of placement).

Equipment: Ensure paver and rollers meet specification and contract requirements. Paving equipment required to be done in one pass and compacted with min 10-ton vibratory roller.

Material Slips: Define who will be collecting material slips from delivery trucks.

Road Logistics: Discuss potential for road closure, road signs or flagging needs.

Compaction: Schedule on-site compaction testing if desired with quarry during material production and just before placement.

Points: Ensure the quarry understands the DSA specification. Ensure the material will be at proper moisture and well mixed BEFORE it is loaded into trucks. Consider talking to loader operator. Ensure the quarry is performing moisture tests to monitor pile. Ensure the quarry that the material certification must arrive with the first load on each day of placement.

DSA Season Preparation



DSA Season Prep

- **What is the DSA Project Checklist?**
- Pre-application
- Pre-Project logistics
- ~30 days prior to placement
- Final Preparations
- DSA Placement

What is the DSA Project Checklist?

- A guide for CD's to plan and implement successful DSA placements as part of a DGLVR project
- Informational only: no NEW required actions.
- Any existing **required** actions are noted as such

Driving Surface Aggregate Project Checklist for Conservation Districts

*This document is intended to serve as a guide for Conservation Districts to plan and implement successful Driving Surface Aggregate (DSA) placement as part of a DGLVR project. This is intended as a guide and is not meant as a list of required actions. Items listed as **required** below are defined in policy or the DSA specification.*

Pre-Application

- **Drainage and base first:** The DGLVR Program's focus is on long-term road and environmental improvements. Projects are **Required** to address any drainage, road base, and environmental issues prior to DSA placement. DSA is NOT required on every project. If used, DSA should be the LAST part of a project after all potential drainage and base improvements have been made.
- **Meet with municipality, preferably on-site to discuss prior to application submittal:**
 - **Discussion points:**
 - **Timing:** application, drainage work, lab testing, placement dates, placement window (April-Sep). Consider letting large fill projects settle for a season before placing DSA (could place DSA as a second contract, local decision up to CD)
 - **Details:** Proposed project length, available budget, DSA depth, width, thickness, and tonnage. Use of paver, **required** for placements of 1,000 tons or more.

DSA Season Preparation



DSA Season Prep

- What is the DSA Project Checklist?
- **Pre-application**
- Pre-Project logistics
- ~30 days prior to placement
- Final Preparations
- DSA Placement

Drainage and base first!!



- DSA is not required on every project
- Program focus is on long-term road and environmental improvements
- **Projects are required to address any drainage, road base, and environmental issues prior to DSA placement**

Meet with the municipality

- **Suggested** An on-site pre-application meeting with the municipality helps to ensure a quality application
- **Discussing Topics:**
 - **Timing:** Application, drainage work, placement date(s), placement season, time for production and testing, etc
 - **Details:** Project length, DSA depth, width, tonnage, available budget, paver, etc
 - **Potential suppliers & placement contractors**
 - **Road preparation:** Drainage, surface prep (fill/grading), etc
 - **Compaction:** Will compaction testing be utilized?

Material Calculation

The formula below is a general guide to the amount of DSA needed based on width, depth, and length of placement.

How much DSA should I order?

DSA Needed =	Road Width	x	Road Length	x	0.04 for 8" loose compacted to 6"
(tons)	(ft)		(ft)		0.03 for 6" loose compacted to 4½"

DSA Season Preparation



DSA Season Prep

- What is the DSA Project Checklist?
- Pre-application
- **Pre-Project logistics**
- ~30 days prior to placement
- Final Preparations
- DSA Placement

Bidding

- Municipalities should follow their standard purchasing, bidding, and payment procedures.
- **Prevailing wage applies to contracted labor when the total value of the project exceeds \$25,000**
- An editable DSA Request for Quote is available on the Center’s website if needed



REQUEST FOR QUOTE (RFQ)

DELIVER, PLACE, AND COMPACT DRIVING SURFACE AGGREGATE (DSA)

(ROAD NAME(S) & ID #)

(NAME OF MUNICIPALITY & COUNTY)

1. SCOPE OF WORK:

_____ (hereinafter referred to as "Owner"), requires services to deliver, place and compact approximately _____ tons of DSA, to

(Project Location – describe exact location of placement)

RFQ: use is optional: editable version on CDGRS website

REQUEST FOR QUOTE (RFQ)

DELIVER, PLACE, AND COMPACT DRIVING SURFACE AGGREGATE (DSA)

(ROAD NAME(S) & ID #)

(NAME OF MUNICIPALITY & COUNTY)

1. SCOPE OF WORK:

_____ (hereinafter referred to as "Owner"), requires services to deliver, place and compact approximately _____ tons of DSA, to

(Project Location – describe exact location of placement)

2. CONTRACT TASKS:

A. Work shall include, but is not necessarily limited to, the furnishing of all labor, superintendence, materials, tools and equipment, miscellaneous items and performing all work necessary to complete all construction to the satisfaction of, and subject to the approval of, the Owner.

3. STATE CONVERSATION COMMISSION (SCC) DSA SPECIFICATIONS:

A. All components of the aggregate mix are to be derived by crushing parent rock material. Contractors **must provide a properly executed SCC DSA Certification Form (attached)** at the time their bid is submitted committing that they can provide DSA material that meets the

Once placement contractor and supplier are determined...

- Schedule target placement date, and a potential back-up date in case of delays. Allow as much time as possible for quarry to make material, sampling and testing. (*Sampling delays, lab back-ups/failures*)
- **DSA Sampling:** *Quarries do not have blanket approval to supply DSA.* The full pile of DSA to be used on the job is required to be sampled and tested by a third-party lab prior to placement
- The pile is approved once passing lab results are obtained

DSA Season Preparation



DSA Season Prep

- What is the DSA Project Checklist?
- Pre-application
- Pre-Project logistics
- **~30 days prior to placement**
- Final Preparations
- DSA Placement

Pre-Construction Meeting

Highly Recommended An on-site pre-construction meeting with the placement contractor and the municipality helps to ensure a quality project by getting everyone on the same page

Pre-Construction Meeting Discussion Points

Trucking Logistics:

- Truck routes
- Number of trucks
- Staging areas (material & equipment)
- Turnaround for trucks to reduce backup length.



Pre-Construction Meeting Discussion Points

Final Road Preparation

- Grading and establishing crown cross-slope (week of placement)
- Establishment of paving notches and keys (just prior to placement)



Pre-Construction Meeting Discussion Points

Equipment

- Ensure paver and roller to be used meet Program and contract requirements
- Paving **must** be done in one pass (full road width) and compacted with a minimum 10-ton vibratory roller



Pre-Construction Meeting Discussion Points

Material Slips

- Define who will be collecting material slips from delivery trucks
- Material slips should be retained in project file



Pre-Construction Meeting Discussion Points

Road Logistics

- Potential road closures
- Need for road construction/safety signs?
- Need for flaggers?



Pre-Construction Meeting Discussion Points

Compaction Testing (optional)

- Discuss use of third party or contractor compaction testing if desired
- Measures actual moisture content of material
- helps for sending wet/dry trucks back
- Also measures percent compaction



Quarry/Supplier Meeting

Highly Recommended Consider meeting with quarry or supplier during production and just before placement

- **Make sure production is on schedule and amount is adequate for sampling/completion of project**
- **Ensure quarry understanding of..**
 - **SCC DSA specification**
 - **Importance of adequate mixing**
 - **Importance of proper moisture**
 - **Consider talking to loader operator as well as QC technician**



Quarry/Supplier Meeting

Highly Recommended Consider meeting with quarry or supplier during production and just before placement

- Make sure production is on schedule and amount is adequate for sampling/completion of project
- Ensure quarry understanding of..
 - SCC DSA specification
 - Importance of adequate mixing
 - Importance of proper moisture
 - Consider talking to loader operator as well as QC technician
- Make sure quarry is doing moisture testing to monitor pile
- Reminder about material cert. on first load delivered



DSA Season Preparation



DSA Season Prep

- What is the DSA Project Checklist?
- Pre-application
- Pre-Project logistics
- ~30 days prior to placement
- **Final Preparations**
- DSA Placement

Week of Placement

- **Review final logistics with municipality, contractor, supplier, trucking provider to make sure all are on the same page**
 - **Road prep (crown, base, drainage)**
 - **Truck routes (power lines)**
 - **Staging areas**
 - **Availability of equipment and personnel**

Week of Placement: Check the Weather



Weather and Cancellations:

The DSA specification states: *“If freezing temperatures or precipitation are forecast that may cause the material to freeze, or prevent the material from drying out, placement shall be postponed at the discretion of the road owner, Conservation District, or aggregate supplier.”*

It will often be up to the Conservation District to make calls to postpone due to weather.

Day before and Day of Placement

- **Contact municipality, contractor, & quarry to verify placement plan**
 - **Include engineering tech performing compaction testing (if done). Their experience level can vary.**
 - **One last check in can eliminate problems**
 - **Use discussion points from above to tie up any loose ends**
- **Check road for crown, keys, notches, etc.**
 - **Irregularities in the road base will reflect to the surface**

DSA Season Preparation



DSA Season Prep

- What is the DSA Project Checklist?
- Pre-application
- Pre-Project logistics
- ~30 days prior to placement
- Final Preparations
- **DSA Placement**


Day of Placement

- Are transport trucks tarped as required?
- Did the first load come with a certification?
 - Required
 - Who is collecting load slips?

During placement

Continuously monitor...

- Placement depth, width, & crown/cross-slope
 - It may take several hundred feet to get the paver “dialed in”
 - Yield?



During placement

Continuously monitor...

- Moisture, adequate mixing of material
 - Be alert for changes in consistency
 - Variations can happen throughout the day



During placement

Continuously monitor...

- Trucking logistics
 - # of trucks
 - Power lines
 - Turnarounds, routes, flaggers, etc.



Water pouring from truck beds...

In its wettest state, DSA should look like very low-slump concrete, better if it's a bit drier than that



Too wet

Too dry

Will not compact

Will come apart quickly



During placement

Making adjustments...

- **Contact quarry to make adjustments.**
 - Use dump truck radios in remote areas
 - Note time of change request and compare to load time on tickets
- ***Send trucks back if necessary!***
 - Once its down on the road surface, its more difficult to fix
- **Visit quarry if necessary**
 - Unforeseen problems like personnel/equipment/moisture issues

During placement

Compaction testing...

Utilizing a nuclear density gauge

- **Not required by Program**
- **Quantitative way to quickly determine**
 - Density (% compaction)
 - Moisture content – to compare to target moisture
- **Having this data can make it easier to send unacceptable loads back to the source**



See DSA Handbook or Full DSA Webinar for details

COMPACTION

DSA Placement

- **Compaction:**

- Compaction should begin when the outer edge of the aggregate begins to dry and become light in color. This could be minutes or hours depending on temperature, sunlight, wind, canopy, and moisture content.
- If excessive material sticks to the drum of the roller, wait for further drying before compaction. In cases where wet material is placed in cold/wet conditions, compaction the following day and beyond is often necessary.
- If you have opted to do compaction testing, compact a small length of DSA for the test to be run. Limit this section to only what is needed for the test if the material is on the wet side.
- **General Compaction Sequence:**
 - **Initial passes over uncompacted DSA should be done in static (non-vibratory) mode.**
 - Subsequent passes should be done in vibratory mode.
 - Do not use vibratory mode when going down steep sections of road or if it brings excessive water and fines to the surface.
 - Overlap passes from the road edge towards the crown.
 - Compact the crown from both sides, but do not “straddle” the crown with the roller.

Thank You! Questions?

Reminder: NEW DSA Project Checklist for CDs

- 3-pages
- Sent in webinar reminder
- Posted online

30 day notice is a minimum

Notify as soon as supplier is known

- Supplier needs time to make entire pile
- Time for sampling
- Time for testing
- Potential time for failures

Surface Aggregate Project Checklist for Conservation Districts
This document is intended to serve as a guide for Conservation Districts to plan and implement successful Surface Aggregate (DSA) placement as part of a DGLVR project. This is intended as a guide and not a list of required actions. Items listed as required below are defined in policy or the DSA specification.

Application

Drainage and base first: The DGLVR Program's focus is on long-term road and environmental improvements. Projects are Required to address any drainage, road base, and environmental issues prior to DSA placement. DSA is NOT required on every project. If used, DSA should be the LAST part of a project after all potential drainage and base improvements have been made.

Meet with municipality, preferably on-site to discuss prior to application submittal:

- Discussion points:
 - **Timing:** application, drainage work, lab testing, placement dates, placement window (April-Sep). Consider letting large fill projects settle for a season before placing DSA (could place DSA as a second contract, local decision up to CD)
 - **Details:** Proposed project length, available budget, DSA depth, width, thickness, and tonnage. Use of paver, required for placements of 1,000 tons or more.
 - **Potential suppliers and placement contractors**
 - **Road preparation:** in addition to drainage, what road surface prep (fill, grading) will need to be done prior to placement, and who will be responsible.
 - **Compaction:** Will compaction testing be utilized (costs can be built into grant application)?

How much DSA should I order?

DSA	Road Width x	Road Length x	0.04	8" loose depth compacted to 8"
			0.03	6" loose depth compacted to 6"

Final Road Preparation: Grading and establishing final crown (week of placement). Establishment of paving notches and keys to support edge of DSA placement (day of placement).

Equipment: Ensure paver and rollers meet specification and contract requirements. Paving required to be done in one pass and compacted with min 10-ton vibratory roller.

Material Slips: Define who will be collecting material slips from delivery trucks.

Road Logistics: Discuss potential for road closure, road signs or flagging needs.

Compaction: Schedule on-site compaction testing if desired with quarry during material production and just before placement.

Points:
job on their schedule and do they have the appropriate amount of DSA.
that the quarry understands the DSA specification.
sure the material will be at proper moisture and well mixed BEFORE it is loaded into
ks. Consider talking to loader operator.
re quarry is performing moisture tests to monitor pile.
quarry that the material certification must arrive with the first load on each day of

ESM Trainings: 12 scheduled statewide with the first one this week in Johnstown.

Stream Crossing Trainings: Conservation Districts

- May 21-23
- June 11-13
- Aug 13-15

Stream Crossing Trainings: Design Engineers

- July 1-2 Centre
- Aug 28-29 McKean
- Sep 18-19 Monroe

Administrative and Financial Trainings

- ~~Mar 13 (Admin), Mar 14 (financial), Berks~~
- May 21 (Admin), May 22 (financial), Westmoreland
- July 23 (Admin), July 24 (financial), Centre
- Oct 16 (Admin), Oct 17 (financial), Luzerne
- Dec 3 (Admin), Dec 4 (financial), Venango

Other Training Notes:

- **Workshop:** Mark your calendars for October 8-10 in Dubois.
- **ESM Boot Camps:** Working on finalizing dates for “new hire boot camps” not held since before COVID. Currently planning for two sessions in September, details to come.
- **DEP Stream Trainings:** Building off the two completed last year, the Center is holding three 1.5 day stream crossing trainings for DEP permit review staff this spring.
- **Course Tracker:** Don't forget the new course attendance tracker allows you to look up your, or anyone else's, current certifications and expiration dates. <https://dirtandgravel.psu.edu/education-training/course-attendance-tracker/>

5-Year Spending Update

- All funding from agreement must be spent out by 6/30/2024
- Current CD Status as of 3/20/2024
 - Spent everything: 27 DGR, 23 LVR
 - Committed everything: 25 DGR, 31 LVR
 - Not committed: 12 DGR, 12 LVR

5-Year Spending Update - Financials

- **Dirt and Gravel**
 - **Committed: \$3,859,654.33**
 - **Not Committed: \$379,227.69**
- **Low Volume**
 - **Committed: \$2,694,288.49**
 - **Not Committed: \$564,217.31**
- **Total that still needs to be spent**
 - **DGR: \$4,238,882.02**
 - **LVR: \$3,258,505.80**
 - **Total: \$7,497,387.82**

5-Year Spending Update

- If you are **Green** in both DGR and LVR, great job!
- If you are **Red** in DGR and/or LVR, you have already been contacted for a status update.
- If you are **Yellow** in DGR and/or LVR, expect follow-up status calls/emails.

Question:

How do I know if I'm red, yellow, or green?

Answer:

If your "balance remaining" is \$0 in your GIS quarterly report, you are **green**

Previous 5-Year Agreement	
"Old Money" Balance: \$	19,690.82
Currently Spent: \$	217,355.40
Balance Remaining: \$	0.00

Question:

How do I know if I'm red, yellow, or green?

Answer:


If you have a "balance remaining," and it is **less than** the committed remaining, you are **yellow**

Spending Status

Unreported Advance: \$	0.00
Unreported Replenishments: \$	0.00
Current Balance: \$	404,139.40
Committed Remaining: \$	203,196.78
Uncommitted Balance: \$	200,942.62

Previous 5-Year Agreement

"Old Money" Balance: \$	269,617.14
Currently Spent: \$	201,283.53
Balance Remaining: \$	68,333.61



Question:

How do I know if I'm red, yellow, or green?


Answer:

If you have a "balance remaining" and it is **greater than** the committed remaining, you are

red


Spending Status		Previous 5-Year Agreement	
Unreported Advance: \$	0.00	"Old Money" Balance: \$	4,443.13
Unreported Replenishments: \$	0.00	Currently Spent: \$	0.00
Current Balance: \$	51,121.09	Balance Remaining: \$	4,443.13
Committed Remaining: \$	0.00		
Uncommitted Balance: \$	51,121.09		

5-Year Spending Status – DGR



5 Year Spending Status

LVR



Question:

How do I make sure my spending is counted towards the spending requirement?

Answer:

Enter admin, edu, and project expenses in the GIS by 6/24/2024 (and don't forget to click save!)

The screenshot shows a web-based form titled "Quarterly Report". At the top, there are dropdown menus for "Select Quarter" and "Select County", followed by a toolbar with various icons. Below this is a navigation bar with tabs for "Dirt and Gravel", "Low Volume", "Activity Report", "Files", and "Managers", along with a "Date Submitted:" field. The main content area is divided into four sections: "Program Income", "Program Expenses", "Balance at District", and "Replenishments". The "Program Expenses" section is circled in red and contains four input fields: "Administrative: \$", "Education: \$", "Projects: \$", and "Other: \$". The "Program Income" section has four input fields: "SCC Advance: \$", "SCC Replenishment: \$", "Interest Earned: \$", and "Other: \$". The "Balance at District" section has one input field: "Starting Balance: \$". The "Replenishments" section has one input field: "Potential Claim: \$".

Question:

What if my expenses won't be ready to enter in GIS by 6/24/2024?

Answer:

Contact Ken or the SCC to discuss a plan

Question:

What if I don't know how much money I need to spend or how to spend it?

Answer:

- Review GIS
- Review past webinars
- Reach out to Ken or the SCC for assistance

Question:

What if I know I'm not going to meet my spending requirements?

Answer:

Reach out to Ken or the SCC to let us know.