

Approved Products List – 12/9/2020

The Dirt & Gravel Road Maintenance Program was founded on solid environmental principles. One of these principles is the program's strict limitations on the use of products that may cause damage to the environment in any way. Listed here are the products approved for purchase and use with program funding. The program does not endorse these or any other individual products.

PETROLEUM EMULSION DUST SUPPRESSANT			
PRODUCT NAME	DISTRIBUTOR	TYPE	APPROVED APPLICATION RATE
Dust Clear G	Midland Asphalt Materials, Inc. 88 Barrett Road Woodland, PA 16881 Phone: (814) 857-7635 www.midlandasphalt.com	Tall Oil Emulsion	2 applications of 0.2 gal/yd ² 15 minutes apart
Resinator	West Gary Momar Incorporated 1830 Ellsworth Industrial Dr. Atlanta Georgia, 30318 Phone: (404) 355-4580 West.gary@momar.com	Petroleum Emulsion	0.5 gal/yd ² of 1:4 emulsion to water or more dilute
Ultrabond 2000	Scott Reefer Environmental Energy Solutions, LLC 10027 Rte. 403 Hwy South Seward, PA 15954 Phone: (814) 446-5625 sreefer@eesolutionsllc.com	Petroleum Emulsion	2 applications of 0.25 gal/yd ² of 1:5 emulsion to water or more dilute

SYNTHETIC FLUID DUST SUPPRESSANT			
PRODUCT NAME	DISTRIBUTOR	TYPE	APPROVED APPLICATION RATE
EnviroKleen	Lynn Cielec Midwest Ind. Supply 1101 3rd Street S.E. Canton, OH 44711 Phone: (800) 321-0699 Cell: (303) 417-2069 Fax: (330) 456-3247 www.midwestind.com	Synthetic Fluid	0.125 gal/yd ² Two passes are required for a total application rate of 0.250 gal/yd ² . No dilution.
DustLess	Rose Cyr Global Environmental Solutions, LLC 395 Main St., Unit 7 Salem, NH 03079 Phone: (978) 388-3312 Fax: (603) 362-9207 www.GlobalEnvironmentalSolutions.com	Synthetic Fluid	Min = 0.18 gal/yd ² . Max = 0.45 gal/yd ² No dilution.

ACRYLIC POLYMER DUST SUPPRESSANT

PRODUCT NAME	DISTRIBUTOR	TYPE	APPROVED APPLICATION RATE
DustREADY 49	Tim Drake Zinkan Enterprises, Inc. 1919 Case Pkwy North Twinsburg, OH 44087 sales@zinkan.com Phone: (800) 229-6801	Acrylic	1:4 dilution of product to water. Two applications of 0.25 gal/yd ²

SOIL STABILIZER

PRODUCT NAME	DISTRIBUTOR	TYPE	APPROVED APPLICATION RATE
EcoRoads	Colby Price EnviRemend Construction 6480 Beach Dr. SW Ocean Isle Beach, NC 28469 Phone: (910) 712-1081 cprice@enviremed.net	Enzyme	diluted with water at ratio of not < 250 to 1 evenly mixed with subgrade to optimum moisture

ROAD FILL MATERIALS

PRODUCT NAME	DISTRIBUTOR	TYPE	
Harsco Minerals	Bob Onyshko Harsco Minerals Phone: (717) 506-2071 1-800-850-0527 ronyshko@harsco.com	Recycled Steel Slag	Road Fill Material

The publishers of this publication gratefully acknowledge the financial support of the PA State Conservation Commission. For additional information or assistance, contact: Center for Dirt & Gravel Roads Studies, Penn State University, 215 Transportation Research Building, University Park, PA 16802 (Toll-Free Phone: 1-866-668-6683, Fax: 814-863-6787, Email: dirtandgravel@psu.edu). Additional copies available on our website at: www.dirtandgravelroads.org. © 2015 Penn State Center for Dirt and Gravel Roads. All rights reserved.